## F10 Series

SINLOIHI COLOR F10 Series is fluorescent pigment of high light stability. It also offers high color brilliancy as well as high solvent stability.

- **Recommendable Applications** 
  - Advertising signboards & displays
  - Signs for ships or harbor facilities
  - Emergency Equipments (Fire extinguishers, fire cars, etc)
  - Silk screen printing ink

## Specifications

Average Particle Size	$3.5 \sim 4.5 \mu$ m
Softing point	130 ∼ 140°C
Solvent stability	Although it can be used with Aliphatic-Hydrocarbons and Xylene solvents, but cannot be used with Aromatic-Hydrocarbons as well as Ester Ether and Ketone solvents neither.
Net weight	10kg
Packaging	Paper bag

## Available Colors





## **NOTES**

A white-undercoat is definitely necessary before applying fluorescent paints in order to secure hiding power as well as color brilliancy.

High light stability is available with fluorescent paints by employing the F10 Series even without a clear overcoat, off course, subject to application and film thickness.



Sales&Marketing Div

Head office/Ofuna Factory 19-12,2-chome,Dai,Kamakura, Phone:81-467-43-2121 19-12,2-chome,Dai,Kamakura, Phone:81-467-43-7755

website: http://www.sinloihi.co.jp E-mail: info@sinloihi.co.jp